

PACKAGED PUMP STATIONS AND CHAMBERS

An extensive range of packaged pump stations and ancillaries, ranging from the 750mm dia. x 1200mm deep MICRO package, through to 2400mm dia. x 6000mm horizontal or vertical stations. These single and twin pump stations can be fitted with many of our single and three phase sewage and grinder pumps, and even ATEX (explosion proof models). Simply let us have details of your application and we will quote the best option, delivered to UK mainland site FOC.

Examples:



MICRO 750 PACKAGED PUMP CHAMBER

This 750mm dia. x 1200mm deep chamber is ideal for small waste or clean water applications. It is generally supplied fitted with our BBC Semisom 450 1.1kW sewage pump capable of handling flows to 500 l/m and heads to 10.5m with 50mm solids handling.

1000mm SINGLE PUMP CHAMBER

Available in depths of 1.5, 2.0, and 2.5m this chamber is suitable for single pump applications with 40mm or 50mm discharge.

Double laminated HD polyethylene chamber.

Ready to install package with control cabinet and alarm.



1250mm TWIN PUMP CHAMBER

Suitable for 50mm, 65mm or 80mm discharge twin pump installations, this chamber is available in depths of 2, 2.5 or 3m.

Double laminated HD polyethylene chamber. Complete, ready to install package with single or three phase pumps and alternating duty/assist control panel and alarm.

1700mm TWIN PUMP CHAMBER

Available in depths of 2.0, 2.5, 3.0 and 3.5m this chamber is suitable for twin pump applications with 65, 80 or 100mm discharge. Double laminated HD polyethylene chamber.

Ready to install package with multi-function control cabinet.



2400mm DIAMETER PUMP CHAMBER

Suitable for vertical or horizontal installation, this heavy duty compressed polymer tank is available in 2m to 6m with capacities from 9,000 to 27,000 litres. Custom made to your exact requirements, it features discharge outlets up to 300mm.



SINGLE DOOR KIOSK - VALVE CHAMBER

Measuring 1200mm high x 750mm wide x 450mm deep, this weatherproof kiosk features a lockable 'winged' handle, polycarbonate hinges and an 800mm x 500mm internal ply mounting board.

This 600mm deep x 800mm wide x 850 or 1000mm long external valve chamber is constructed from high density linear polyethylene and is supplied with a 5 tonne / 4 screw galvanised access cover.



© Descriptions, technical data and features contained in this leaflet are not binding. We reserve the right to make any necessary modifications without prior notice.

